Commercial Pool Code in Denton

Have you ever wondered what the inspector was looking for when your commercial pool was being inspected? Here is a general checklist that should help with the most commonly inspected items.

Water Chemistry/Quality

	SPAS	POOLS
Chlorine*	1-8 PPM	2-8 PPM
Bromine*	2.5-12 PPM	4.5-12 PPM
pН	7.0-7.8	7.0-7.8
CYA	Max 100ppm	Max 100
Temperature	e N/A	104 F Total
Alkalinity	60-180 PPM 60-1	80PPM

*Measured as free available sanitizer using DPD method. Water must be clear, free of debris and algae, and the bottom of the deepest water must be visible. Maintain records of daily chemistry checks.

Safety Equipment

- Rescue tube or 15-24" ring buoy with rope; rope length must be 2/3 max. width of pool.
- Life Pole-12ft., non-conducting material with body hook or shepherd's crook, nontelescopic.
- Backboards (Class A & B; C with diving boards) or if lifeguard present.
- First Aid Kit (Class A & B; recommended for C).
- Phone Accessible (within 200 Ft. of pool)
- Provide Safety equipment for each 2,000 sq. ft. of surface.

Gates & Fencing

Gates must be self-closing and self-latching:

- Not easily climbable
- Gate latch not accessible
- Gates open away from pool/spa
- Minimum 4 ft. height

General

- Pool area must be maintained in a sanitary manner
- Chemicals must be properly stored, labeled and used in accordance with label instructions
- Tiles and surfaces must be in good repair and clean.
- Ladders & handrails secure; good repair
- Flow meter and gauges required
- Suction entrapment hazard must be mitigated
- Animals prohibited except service animals
- No glass containers in pool area
- Color coding on pipes required for new; recommended for existing

Filtration Avg.

Depth >4 ft.	Turnover Every
<4 ft.	6 hours Every 6
Avg. depth 1.5	hours Every 30
Spa	min. Every 30
	min.

Flowmeter, filter inlet & outlet & pump suction gauges required. Place pump suction gauge as close to suction side of pump as possible.

Signs & Warnings

- Load limits posted for spas; recommended for pools
- "No Lifeguard on Duty" signs posted
- Rope & float lines @ shallow-deep water transitions (5ft or deeper)
- Supervision of children by adults required
- "No Diving" warning sign (4" letters)
- Location of phone; Emergency/911 number

Additionally spa signs required:

- Max temperature (104 F)
- Warning for "at risk" persons e.g. pregnant women, those taking certain medications, heart conditions, etc.

Depth Markings/No Divin Signspools and spas

Depth Markings

- 4" letters, on deck and sidewall
- Not more than 25 ft. apart, in feet and inches
- Minimum of two signs, placed at max. and min. depth or where shape deviates and depth changes occur

No Diving Warnings

- Mounted on the deck & in pool area (pools)
- Contrasting colors
- 4 inch letters or larger
- Not more than 25 feet apart
- Minimum of two warnings
- Required for water 6 feet or less
- Universal symbol must be used in addition to worded signs

Closure

- Sanitizer not at minimum levels or at excess levels
- Pool clarity or filtration equipment failure
- Suction entrapment or other hazards representing an imminent threat to health and safety of swimmers

Turnover rate:	_gal./min x 60 minutes
X 6 turnovers =	gal.
(Turnover/6 hours)	

The information contained within this brochure is a general check list that many city's use to inspect a commercial swimming pool. If you have any questions concerning your particular situation please consult with your local health department.

COPYRIGHT 2015 Gohlke Pool Supply, Inc. and Gohlke Custom Pools. Inc.